EPA Region 9 Vapor Intrusion Sampling Plan Site-Specific Addendum

Site Name/Location: Middlefield-Ellis-Whisman (MEW) Superfund Area, Mountain View, Santa Clara County, CA

Project Name: MEW OU1 Sewer Pathway Assessment

Anticipated Field Sampling Dates: July 13 - 24, 2020 (5 - 7 days) one-day trips, local travel, no lodging HAPSITE screening (4 - 5 days); TO15 canister and TO 17 passive sampler deployment (4 - 5 days)

Approvals	Name	Signature	Date
Superfund Project Manager	Alana Lee	Alana See	7/8/2020
Region 9 QA Office Reviewer	Lilian Abreu	LILIAN ABREU	Digitally signed by LILIAN ABREU Date: 2020.07.14 11:18:57 -07'00'
Region 9 QA Manager	Audrey L. Johnson	Audrey L Johns	Digitally signed by Audrey L On Johnson

Date: 2020.07.13 11:34:34 -07'00'

Project Description and Background

The EPA MEW Superfund site team is conducting a sewer pathway assessment to evaluate the TCE sewer-to-indoor air pathway at the Middlefield-Ellis-Whisman (MEW) Superfund Site in Mountain View, Santa Clara County, CA. High concentrations of TCE vapors (>1,000 micrograms per cubic meter – $\mu g/m^3$) in the Fairchild sanitary sewer main (Fairchild sewer), a 24-to-27-inch pipeline, are entering into a new sewer lateral (an 8-inch line along private street Ariana Place) within the Waverly residential development (former 277 Fairchild Drive property). EPA collected sewer pathway data May 6 – 11, 2020 indicating TCE vapors in the sewer are entering into the sewer cleanouts and in the residential indoor air space of several newly constructed unoccupied homes at concentrations exceeding EPA TCE accelerated (2 $\mu g/m^3$ and urgent (6 $\mu g/m^3$) response action levels.

The primary source of TCE in the Fairchild sewer is from the regional MEW shallow TCE groundwater plume infiltrating directly into the Fairchild sewer main due to cracks and sags in the sewer line (bottom of the pipeline ranges between 12.5 feet (at Ellis Street) to 22.7 feet below ground surface (at Leong Drive). TCE was detected in Fairchild line sewage (water) samples at three locations collected March 27-28, 2014 (1) upstream near Ellis Street (1.8 - 7.3 μ g/L TCE), (2) near Fairchild Dr/Whisman Rd intersection (29.4 -77.5 μ g/L TCE), and (3) downstream at 159 Fairchild Dr (16 - 36 μ g/L TCE). Sewer gas samples along Fairchild Drive 2014-2020 have consistently shown TCE concentrations in the low hundreds to low thousands (μ g/m³) TCE. Other case studies and recent 2020 sewer gas data in the MEW area indicate considerable variability (one to two orders of magnitude) at the sewer lateral and cleanout air such that it is difficult to predict exactly when and where high TCE concentrations will occur and intrude into the indoor air space.

EPA, in coordination with the City of Mountain View, has identified additional properties/buildings with direct sewer connections and laterals to the Fairchild sewer main that may impact over 120 residences and 12 commercial office buildings.



Sanitary Sewer Lines and Flow – MEW Area and Vicinity

Field Staff and Contact Information

Name	Agency/Organization	Project Role	Phone /Email
			415.972.3141 / Mobile: 415.317.0406
Alana Lee	EPA R9 Superfund	Project Manager	Lee.Alana@epa.gov
			415.972.3799 / Mobile: PRVY-Controlled/Privacy
Mathew Plate	EPA R9 QA Office	VI QA Officer/VI Technical Support	Plate.Mathew@epa.gov
			510.412.2388 / Mobile: PRVY-Controlled/Privacy
Bob Hopeman	EPA R9 FASP	HAPSITE Field Analysis / Sampler	Hopeman.Bob@epa.gov
			510.412.2354 / Mobile: PRVY-Controlled/Privacy
Junn Masongsong	EPA R9 FASP Contractor - ICF	HAPSITE Field Analysis /Sampler	Junn.Masongsong@icf.com
			415.947.4218 / Mobile: PRVY-Controlled/Privacy
Ray Chavira	EPA R9 Superfund	Field Sampler / Support	Chavira.Raymond@epa.gov
			415.972.3064 / Mobile: PRVY-Controlled/Privacy
Michael Schulman	EPA R9 Superfund	Field Sampler / Support	Schulman.Michael@epa.gov
Jess Caldeira	EPA R9 FASP Contractor - ICF	Field Sampler / Support	Jess.Caldeira@icf.com

Conceptual Site Model (select all that apply)

Conceptual Model	Types and approximate number of Sample Location to be Collected (X) / Optional (O						ional (O)			
X Vapors are potentially traveling through a preferential pathway (sewer pipe conduit)	Χ	Main Sewer Air	X	Lateral Sewer Air	Х	Sewer Cleanout Air	0	Indoor Air	Х	Outdoor Air
X Site-contaminated groundwater is infiltrating into the Fairchild sewer upstream of manhole F6-010	Х	Main Sewer Air	Х	Lateral Sewer Air	0	Sewer Cleanout Air	0	Sewer Liquids (sampling by POTW?)		
O Temporally variable vapor migration through unidentified pathways	0	Continuous Pathway Air	0	Tracer Analysis	0	Pressure Analysis	0	Indoor Air		

Sampling Design (See attached maps for Proposed Sampling Locations)

Sewer Pathway Assessment / Fieldwork connected to Fairchild Trunk

This sewer pathway assessment of all the residential properties with connections and laterals to the Fairchild Trunk is time critical because of the high potential TCE risk of the sewer-to-indoor air pathway with similar conditions as observed at the new residential development at the former 277 Fairchild Drive property.

<u>Scope</u>: TCE screening of all safely accessible sewer manholes along Fairchild Drive and laterals (Wiley Terrace, Sonoma Terrace, Cinnamon Circle, Ariana Place and part of Whisman Road, National Avenue, Tyrella Avenue, Leong Drive) and step-ins/step-outs (sewer cleanouts). TO15 canister and TO17 passive sampling of subset for confirmation and predictive sewer transport modeling impacts.

All sampling will be performed in accordance with the Sampling and Analysis Plan for Indoor Air, Outdoor Air, Treatment System, Sub Surface Soil Gas and Sub-Slab Soil Gas Sampling at EPA Region 9 Superfund Sites, August 2017, prepared by EPA Region 9 Superfund Division, including associated EPA Region 9 Standard Operating Procedures (SOPs).

Contingent Accelerated Response Action / Mitigation Measures: If at any time during the sampling assessment, data indicate the potential for TCE indoor air levels of occupied homes are exceeding the accelerated response action level of 2 ug/m3, air purifiers (air treatment units) on each floor of occupied residences and/or expedited confirmation indoor air may be needed. EPA RPM will notify management, consult with project team, conduct outreach, and implement accelerated response actions, as needed.

Number of and Type of Samples

Type of Sample	Sampling	Analytical	Numb	per of Samples	Special Requirements		
	Duration	Method(s)	Primary	QA Samples Duplicates/Blanks*			
	Grab	TO-15	Up to 10	Duplicate/co-located	Sample through venthole of manhole cover.		
Sewer Gas	1-7 day	RAD 130 / TO-17	Up to 50	samples for each analytical method will be collected at a	Target 2- 3 feet below ground surface using tubing/string/wire.		
	Real-Time	Chrom / CRD	Up to 60	frequency of 10 %			
Sewer Cleanout	Grab	TO-15	Up to 10	Duplicate/co-located samples for each	At sewer cleanout with closed cap/lid. Target 6 inches – 1 ft below cap/lid using		
Gas	1-7 day	RAD 130 / TO-17	Up to 50	analytical method will be collected at a	tubing/string/wire.		
	Real-Time	Chrom / CRD	Up to 120	frequency of 10 %			
Indoor Air	24 hour	TO-15 SIM	Up to 10	Duplicate/co-located samples for each analytical method	In currently unoccupied space.		
	3-7 day	RAD 130 / TO-17	Up to 10	will be collected at a frequency of 1 per 10			
	Real-Time	Chrom / CRD	Up to 10	samples			
	24 hour	TO-15 SIM	Up to 5		For comparative purpose.		
Outdoor Air	3-7 day	RAD 130 / TO-17	Up to 5		Representative outdoor ambient air.		
	Real-Time	Chrom / CRD	Up to 5				
Dathway	Grab	TO-15	Up to 5	Duplicate/co-located samples for each	Near potential pathway in currently unoccupied accessible space.		
Pathway	24 hour	TO-15 SIM	Up to 10	analytical method will be collected at a	, p		
	1-7 day	RAD 130 / TO-17	Up to 10	frequency of 10 %			
	Real-Time	Chrom / CRD	Up to 10				


Notes:

^{*}One field/trip blank per shipment for the Radiello 130 and TO-17 samplers will be collected.


Compounds of Potential Concern, Indicators, and EPA Screening Levels – MEW Area


Compound	Indoor Air Cleanup - Chronic (μg/m³)	Indoor Air - Short-term (µg/m³)	Sewer Main/Lateral/ Cleanout (μg/m³)	Notes
TCE	1	2 (accelerated) 6 (urgent)	>33 Sewer main / Lateral	Step-in/out to nearby sewer cleanouts and manholes
			>20 Sewer Cleanout	Step-out to nearby sewer cleanouts. May recommend sewer gas pre-emptive mitigation and/or expedited confirmation indoor air results
	Potential Pathway Air: >1			Confirmation pathway and indoor air samples if accessible/unoccupied
PCE (optional)	0.4			
Cis-1,2-DCE (optional)	60			Indicator (Site-related attribution)
Trans 1,2-DCE (optional)	60			Indicator (Site-related attribution)
Vinyl Chloride(optional)	0.2			Indicator (Site-related attribution)
Chloroform (optional)				Indicator – sewer / tap water


special Project Requirements							


















Example video: F6-037 to F6-035









DRAFT TCE Results For Discussion Purposes Only

Sample Location Type Sewer cleanout (SC) Sanitary Sewer (SS) Manhole (MH) Indoor Air (IA)



Location ID
AROMA Data
HAPSITE Data
Radiello Data
TO15 Data/
TO15 SIM Data

XX-YY		
5/6	11	Sample Date -
5/7	10	TCF con contration
ZZ-3d	12	TCE concentration, μg/m3
5/8	8	



PRVY-Controlled/Privacy